#### www.duetta94.com

# **Checklist for season start Duetta 94**

#### 1. Work to be done ashore

Work	Materials and tools	dono
	needed	done
Antifouling	☐ Antifouling	
_	☐ Painters tape	
	paint roller	
	paint tray	
	☐ Goggles	
	☐ Gloves	
Clean the propeller and paint it with	☐ Sandpaper	
Antifouling	☐ VC Prop o Drev	
Clean the hull and apply wax	□ Wax	
	□ Rag	
	☐ GRP cleaner	
	☐ Sponge	
Clean sewater cooling inlet		
Check the lamps in the mast		
Check standing rigg		
Lubricate the pulleys in the mast	□ WD 40	
Check the sacrificial anode and replace it if	☐ Two zinc anodes	
necessary	☐ Sealings	
-One fitted above the gear box	☐ jaw spanner 24 mm	_
-One on the starboard side of the engine	☐ Teflon tape for sealing	
Check the oil level of the engine		
Check the oil level of the gear box		
Check the tension of the V-belt		
Change the diesel filter at the engine	☐ Filter	
( I do this every two years )		
Check / change Impeller	☐ Impeller	
(I change it every two years )		_
Lubricate the rubber gland seal	☐ Volvo grease	
Clean the diesel filter in the locker		
Vent the diesel system		
Clean and lubricate the winches	☐ Petroleum	
( 1 :6	☐ Grease for winches	
( only if necessary)	□ Bowl	
	☐ Toothbrush	
	☐ Gloves	
Clean and lubricate the rigging screws	☐ Petroleum	
	☐ Grease for winches	
	☐ Gloves	
Change the sacrificial anode at the shaft	☐ Sacrificial anode for a shaft	
	diameter of 25 mm	

## www.duetta94.com

### 2. Work to be done offshore

Work	Materials and tools needed	done
Bleed the rubber gland seal		
Put some oil for babies in the toilet and pump it out	☐ Oil for babies	
Order an expert to check the gas equipment (In Germany every two years necessary)		